

XCC 400H



SPECIFICATIONS:

Package	: PLCC
Leads	: 32 – 48 Pins
Tube Length	: 400 – 600mm
Auto-Loader	: 35 Tubes
Auto-Unloader	: 35 Tubes
Manual Unload	: 4 Tubes
Contact Method	: PLCC Socket
Interface Signal	: START, EOT, BIN1-8
UPH	: 3,200 maximum
Temperature Range	: 20 to 100 °C
Air	: 4 -6 kg/cm ²

DIMENSIONS:

170 x 60 x 180cm (LxWxH)

WEIGHT:

120kg

FEATURES :

- Simplicity
- Reliable
- Easy to maintain
- Ease of operation
- Auto-Loader and Unloader
- 2 buffer track for High Temperature Testing
- Temperature control is by 3 TIC PID Controller
- One of the most cost effective handler in the industry
- Multiple language operation interface
- Troubleshooting is easy with LCD panel displaying problem area
- Ergonomic Design with LCD Panel within comfortable visual range
- Adjustable interface pulse



SINGAPORE/INDIA/INDONESIA/MALAYSIA
Howard Goh
Tel : +65-91848151
Email : howard@xceltronic.com

PHILIPPINES
Romy Manese
Tel : +63-9195837841
Email : romy@xceltronic.com

THAILAND
Rachar Chuchuen
Tel : +66-865648884
Email : rachar@xceltronic.com